

Material Safety Data Sheet



OASIS PRO 53 UP N AWAY FABRIC ODOR ELIMINATOR

Section 1. Chemical product and company identification

Trade name : OASIS PRO 53 UP N AWAY FABRIC ODOR ELIMINATOR
Product use : Air Freshener
Supplier : Ecolab Inc. Institutional Division
370 N. Wabasha Street
St. Paul, MN 55102
1-800-352-5326
Code : 903485-01
Date of issue : 25-August-2005

EMERGENCY HEALTH INFORMATION: 1-800-328-0026
Outside United States and Canada CALL 1-651-222-5352 (in USA)

Section 2. Composition, Information on Ingredients

| <u>Name</u> | <u>CAS number</u> | <u>% by weight</u> |
|--|-------------------|--------------------|
| phosphonic acid, (1-hydroxyethylidene)bis-, potassium salt | 67953-76-8 | 5 - 20 |
| Ethanol | 64-17-5 | 1 - 5 |
| sodium n-(2-carboxyethyl)-n-(2-ethylhexyl)-.beta.-alaninate | 94441-92-6 | 1 - 5 |
| poly(oxy-1,2-ethanediyl), .alpha.-(3-carboxy-1-oxosulfopropyl)-.omega.-hydroxy-, c10-16-alkyl ethers, disodium salts | 68815-56-5 | 1 - 5 |

Section 3. Hazards identification

Physical state : Liquid. (Liquid.)
Emergency overview : CAUTION!

COMBUSTIBLE LIQUID AND VAPOR.
VAPOR MAY CAUSE FLASH FIRE.
Repeated or prolonged contact with irritants may cause dermatitis.
MAY CAUSE EYE IRRITATION.
Avoid contact with skin and clothing. Avoid breathing vapor or mist. Keep away from heat, sparks and flame. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Potential acute health effects

Eyes : Slightly irritating to the eyes.
Skin : Slightly irritating to the skin.
Inhalation : Slightly irritating to the respiratory system.
Ingestion : No known significant effects or critical hazards.

See toxicological information (section 11)

Section 4. First aid measures

Eye contact : In case of contact, immediately flush eyes with plenty of water. Remove contact lenses and flush again. Get medical attention if irritation occurs.
Skin contact : Wash with soap and water. Get medical attention if irritation develops. Wash clothing before reuse.
Inhalation : If inhaled, remove to fresh air.
Ingestion : Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.

Section 5. Fire fighting measures

- Flash point** : 60 °C (Closed cup)
Fire fighting media and instructions : In case of fire, use water spray (fog), foam, dry chemicals, or CO₂.

Dike area of fire to prevent product run-off.
 Combustible liquid and vapor. Vapor may cause flash fire. Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

- Special protective equipment for fire-fighters** : Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full facepiece operated in positive pressure mode.

Section 6. Accidental release measures

- Personal precautions** : Immediately contact emergency personnel. Eliminate all ignition sources. Keep unnecessary personnel away. Use suitable protective equipment (Section 8). Do not touch or walk through spilled material.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Methods for cleaning up** : If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.--

Section 7. Handling and storage

- Handling** : Keep away from heat, sparks and flame. To avoid fire, minimize ignition sources. Wash thoroughly after handling.
- Storage** : Keep out of the reach of children. Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).
 Store between -10 and 50°C

Section 8. Exposure Controls, Personal Protection

- Engineering controls** : Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

Personal protection

- Eyes** : No protective equipment is needed under normal use conditions.
Hands : No protective equipment is needed under normal use conditions.
Skin : No protective equipment is needed under normal use conditions.
Respiratory : No protective equipment is needed under normal use conditions.

Name

ethanol

Exposure limits

ACGIH TLV (United States, 1/2004).

TWA: 1880 mg/m³ 8 hour(s). Form: All forms

TWA: 1000 ppm 8 hour(s). Form: All forms

OSHA PEL (United States, 8/1997).

TWA: 1900 mg/m³ 8 hour(s). Form: All forms

TWA: 1000 ppm 8 hour(s). Form: All forms

Section 9. Physical and chemical properties

- Physical state** : Liquid. (Liquid.)
Color : Clear.
Odor : Fragrance like.
pH : 7.75 (100%)
Specific gravity : 1.095 (Water = 1)

Section 10. Stability and reactivity

Stability : The product is stable.
Reactivity : Slightly reactive to reactive with acids, alkalis.

Section 11. Toxicological information

Potential acute health effects

Eyes : Slightly irritating to the eyes.
Skin : Slightly irritating to the skin.
Inhalation : Slightly irritating to the respiratory system.
Ingestion : No known significant effects or critical hazards.
Chronic effects on humans : Contains material which causes damage to the following organs: blood, the reproductive system, liver, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Section 12. Ecological information

Products of degradation : These products are carbon oxides (CO, CO₂) and water, nitrogen oxides (NO, NO₂ ...), phosphates. Some metallic oxides.

Section 13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Consult your local or regional authorities.

Section 14. Transport information

| Regulatory information | UN number | Proper shipping name | Class | Packing group | Additional information |
|------------------------|----------------|----------------------|-------|---------------|------------------------|
| DOT Classification | Not regulated. | - | - | - | - |

APPLIES ONLY DURING ROAD TRANSPORT

Any variation of the shipping description based on the packaging is not addressed.

Section 15. Regulatory information

HCS Classification : Combustible liquid
 Target organ effects

U.S. Federal regulations : SARA 302/304/311/312 extremely hazardous substances: None.
 SARA 302/304 emergency planning and notification: None.

TSCA 8(b) inventory : All materials are listed or exempt.
California prop. 65 : No products were found.

Section 16. Other information

| | | |
|--|---------------------|----|
| Hazardous Material Information System (U.S.A.) : | Health * | 1 |
| | Fire hazard | 2 |
| | Reactivity | 0 |
| | Personal protection | -- |

Date of issue : 25-August-2005.
Responsible name : Regulatory Affairs
Date of previous issue : No Previous Validation.

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.